


## Silicone Free Thin Film

### SFT Series

This material is suitable where there are concerns about the use of Silicones. Our Silicone free materials use a ceramic filled Polyurethane. They have a high thermal conductivity with good electrical insulation properties. Available with one side adhesive coating. Can be supplied die-cut to customer's specification.



#### PRODUCT APPLICATION

- Medical Applications
- Laser Equipment
- LED's
- Aerospace
- HDD
- Automotive

Specification	SFT80-XX(-T1)	SFT90-XX(-T1)
Thermal Conductivity (W/m.k)	1.8	6.0
Thickness (mm)	0.15/0.30	0.10/0.12/0.30
Thermal Resistance (K/W)	0.20	0.09
Thermal Impedance (°C*cm <sup>2</sup> /W)	73	33
Density (g/cm <sup>3</sup> )	2.26	1.46
Break down voltage (kV)	4	4 (0.12 ~ 0.3mm)
Dielectric Break down voltage (kV/mm)	25	25
Tensile Strength (N/mm <sup>2</sup> )	3.0	2.5
Elongation (%)	130	150
Temperature range (°C)	-40~+125	-40~+125
Standard sheet size (mm)	250 x 225	250 x 225
Available with adhesive	1 Side (-T1)	1 Side (-T1)
Colour	Blue	Light Blue

#### AMEC Thermasol

1-2 Steam Mill Lane, Great Yarmouth, Norfolk, NR31 0HP

**Telephone:** +44(0) 1493 668622      **Fax:** +44(0) 1493 668623

**Email:** [sales@amecthermasol.co.uk](mailto:sales@amecthermasol.co.uk)      **Website:** [www.amecthermasol.co.uk](http://www.amecthermasol.co.uk)