

## WG-35NS

A Non-Silicone thermal pad, which uses of soft acrylic as base material filled with a thermally conductive ceramic powder. It has good thermal conductivity with high break down voltage. It does not contain any silicone molecular outgassing which will contaminate lens or electrical.



### PRODUCT FEATURES

- NO MW Siloxane.
- Great heat conductivities, good insulation.
- Great for shock resist and gap sealing.

### PRODUCT APPLICATION

- Cellphone, Tablet, Notebook, PCB, Chipset, LCD.
- Router, Disk drive, GPS, Game Device.
- Masking Device, Test Equipment, Military.

Item	Unit	Specification	Test Method
Thermal Conductivity	W/m.k	3.0	ASTM D5470
Hardness	Shore 00	78	ASTM D2240
Thickness	mm	0.5~10.0	ASTM D374
Specific Gravity	g/cm <sup>3</sup>	2.2	ASTM D792
@1.0mm Volume Resistivity	ΩCM	10 <sup>10</sup>	GB/T 1410
Adhesive	/	/	
<b>Self-adhesive</b>	Double Sided	Double Sided	
Breakdown Voltage	kV / mm	>6	ASTM D149
Flammability Class	/	UL94 V-0	UL-94
Max Temperature Range	°C	-40~+200	-
Colour	-	White	Visual

AMEC Thermasol

1-2 Steam Mill Lane, Great Yarmouth, Norfolk, NR31 0HP

Telephone: +44(0) 1493 668622 Fax: +44(0) 1493 668623

Email: [sales@amecthermasol.co.uk](mailto:sales@amecthermasol.co.uk) Website: [www.amecthermasol.co.uk](http://www.amecthermasol.co.uk)